

EDILIA 2

- Struttura in acciaio zincato
- Tecnologia costruttiva a taglio laser
- 7 tipologie di telai perimetrali
- 2 profili di compensazione
- Serratura (singola per la versione ad 1 anta, doppia per la versione a 2 ante). Ambedue le versioni sono corredate di un singolo puntale di chiusura (superiore / inferiore) con trattamento antitaglio. Mezzo cilindro a profilo europeo antitrapano solita cifratura di serie per singola commessa
- Verniciatura a polveri poliestere per esterno per una perfetta aderenza e durata delle vernici
- Ogni fornitura include Kit d'uso e manutenzione
- Tutti i modelli di grate sono realizzati da moduli di acciaio pieno di spessore 14 mm

- *Galvanized steel structure*
- *Laser cutting constructive technology*
- *7 types of perimeter frames*
- *2 compensation profiles*
- *Lock (single for 1 door version, double for 2 door version). Both versions are equipped with a single locking tip (upper / lower) with anti-cut treatment. Half anti drill european cylinder, same standar encryption for single order*
- *Polyester powder coating for outdoor use for perfect adhesion and durability of the paints*
- *Each supply includes a Service Kit and Maintenance Kit*
- *All security bar models are manufactured with solid steel modules with a thickness of 14 mm*



Certificazione
Antieffrazione
Break-in resistance



Modelli disponibili
4 available models



Speciale snodo
autobloccante
Special self-locking joint



Kit
manutenzione
Maintenance kit

KIT PER SERRATURA *LOCKING KIT:*



Cilindro di sicurezza K2
Safety cylinder K2



Chiave di cantiere
Construction site key



3 chiavi padronali
3 keys



Tesserina di duplicazione chiavi
Duplication keys card

Prodotto certificato:



Le nostre certificazioni:

www.errecisicurezza.com/certificazioni/



ERRECI SICUREZZA S.r.l.

Viale dell'Industrie, 5/7 - 26845 Codogno LODI
Tel. +39 0377 436041 - 379937 - 433126
Fax +39 0377 437928
info@errecisicurezza.com

www.errecisicurezza.com



EDILIA²

CLASSE 2 ANTIEFFRAZIONE

EDILIA 2



EDILIA²



Snodo autobloccante doppia funzione APERTURA INTERNA ED ESTERNA

Le versioni ACS 180 sono dotate di un particolare snodo, che ha una doppia funzione, in apertura di ribaltare l'anta completamente verso l'esterno, in chiusura di autobloccarsi con il telaio tramite un perno d'acciaio cabonitrurato, offrendo ulteriori punti di ancoraggio antistrappo. Tramite lo snodo otteniamo una totale apertura anche verso l'interno del locale, rendendo agevole l'operazione di chiusura della spagnoletta della persiana o antone.

Self-locking joint double function OPENING INTERNAL AND EXTERNAL

The ACS 180 versions are equipped with a special articulated joint, which has a twofold function, in the opening stage, it overturns the panel completely towards the exterior, in the closing stage it locks itself with the frame through a carbonitrided steel pin and it also offers anti-rip out anchorage points. Thanks to its articulated joint allows obtaining a complete opening also towards the interior of the room, making opening window bolt of the shutter or large panel, easier.



Posizione: Chiusa
Position: Closed



Posizione: Apertura totale interna
Position: Total internal opening



Posizione: Apertura totale esterna
Position: Total external opening

La caratteristica della grata "Edilia 2" è la struttura resa semplificata. La grata è realizzata da un telaio perimetrale di acciaio zincato di sezione 30x30x2 mm di spessore. I telai perimetrali sono disponibili in 7 diverse tipologie, per offrire l'apertura più adatta alle proprie esigenze. La particolare conformazione della grata determina un ingombro complessivo di soli 35mm, permettendo l'applicazione anche in presenza di monoblocchi evitando modifiche ad infissi esistenti.

The distinguishing feature of the "Edilia 2" security bar system is its streamlined structure. The security bar system consists of a perimeter frame in galvanized steel with a 30x30 mm section and 2 mm thick. The perimeter frames are available in 7 different versions to offer the most suitable opening for your needs. Its particular structure leads to an overall size of just 35mm, allowing its use even in presence of mono-blocks with no need to make changes to existing windows.



Defender esterno per cilindro passante
External Defender for passing cylinder



Particolare snodo
Hinge detail



Puntale di chiusura superiore/inferiore
Closure tip upper/lower



Mezzo cilindro
Half cylinder

